



KEY INDUSTRIAL HOSE

KIH RWS 150

Size : 2" - 12"



Application: Water suction and discharge in industrial and construction services.

Tube: Natural and Synthetic Rubber

Cover: Abrasion and weather resistant synthetic rubber

Temperature: -22°F to + 185°F

Reinforcement: High tensile synthetic textile and steel helix wire

KIH ORANGE/CLEAR

Size : 2" - 12"



Application: Water suction and rental/construction pumping

Construction: Flexible PVC, rigid PVC helix, synthetic braiding, smooth bore, corrugated O.D.

Temperature: -13°F to + 140°F

KIH TANK TRUCK 150

Size : 2" - 8"



Application: For use on tank trucks, bulk petroleum stations and in- plant oil service

Tube: Oil resistant, black conductive Nitrile(NBR)

Reinforcement: Synthetic textile and helix steel wire

Cover: Black, abrasion, ozone, weather, heat and oil resistant neoprene rubber

Temperature: Suitable for use in the range -31°F to 180°F

Branding: KIH Tank Truck 150

Couplings: Contact KIH for coupling recommendation

OIL SERVICES & DISCHARGE CARGO HOSE

Size : 4" - 18"



Application: For oil/water suction and delivery service

Tube: Oil and fuel resistant conductive nitrile (NBR)

Cover: Oil, weather and ozone resistant, wrapped cover, black synthetic rubber

Temperature: -40°F to +194°F

Reinforcement: Multiple high tensile synthetic tire cords (polyester cords) with steel wire helix

Lengths: 10' and 20' standard lengths

Couplings: Built-in pipe flanges fixed x floating

KIH COMPOSITE 250

Size : 4" - 12"



Application:Suction and Discharge of Water, Gasoline, Diesel fuel, Paraffin, Kerosene, Lubricating Oils, 100% aromatics, black oils and heavy lubricants and solvents.

Carcass:Multiple layers of polypropylene fabric, film and polyester barrier layers

Reinforcement:High tensile strength galvanized inner and outer wire

Temperature:-22°F to +176°F(-30°C to +80°C)

Cover:Abrasion resistant PVC impregnated fabric

KIH SS 700 METAL HOSE

Size : 2" - 12"



Construction: SS 316L Corrugated Flexible Hose with SS 304 Double Wire Braiding

Couplings: TIG Welded with 150# SS 316 Swivel Flanges at both ends with SS 316 Sch.40 Stub end.

KIH CHEM HOSE

Size : 2" - 6"



Tube:Clear Ultra High Molecular Weight polyethylene

Cover: Green abrasion resistant green EPDM

Reinforcement: Multiple plies of high tensile textile with dual helix

Temperature: -40°F to +250°F



KEY INDUSTRIAL HOSE

OIL NITRILE 150 DISCHARGE HOSE

Size : 2" - 12"



Tube: Blend of synthetic elastomers, smooth, oil resistant, black
Reinforcement: Single high tensile textile braid
Cover: Blend of synthetic elastomers compound, ribbed finish
Temperature: Suitable range -4°F to 176°F
Lengths: 100 ft. standard lengths
Colors: Black, Orange, Red or Yellow

KIH RED PVC DISCHARGE HOSE

Size : 2" - 12"



Application: Use for agricultural, quarry, irrigation, mining construction and industrial applications
Tube & Cover: Premium Red PVC
Reinforcement: Two spiral plies and longitudinal silk cords
Temperature: -10°F to 150°F
Packaging: Cut and coupled to length
Couplings: Standard short shank aluminum, malleable or brass couplings, Steel Bauer

KIH BLUE PVC DISCHARGE HOSE

Size : 2" - 4"



Application: Use for light duty, general purpose agricultural, irrigation, and construction applications.
Tube & Cover: Blue PVC
Reinforcement: Polyester yarn
Temperature: -4°F to 150°F
Packaging: Cut and coupled to length

KIH MILL HOSE

Size : 2" - 4"



Application: Medium pressure water discharge hose
Tube: SBR
Cover: 100 % Polyester
Temperature: -25°F to 185°F
Lengths: 50 ft. and 100 ft. stock lengths
Color: White
Couplings: Camlock or Water Shank or NST

KIH TPU DISCHARGE HOSE

Size : 6" - 16"



Application: Water transfer, Oilfield, Fracking
Tube & Cover: TPU, Smooth cover, extruded through the weave.
Reinforcement: Circular woven filament polyester yarn.
Temperature: -58°F to +176°F

KIH BULL HOSE

Size : 2" - 4"



Application: Heavy Duty air hose for use in mines, construction and industrial applications where maximum service is required
Tube: Blend of SBR and NBR, black, smooth, suitable for water and air, resistant to oil mist
Cover: Blend of EPDM and SBR, yellow, smooth with cloth impression, weather, ozone and abrasion resistant
Reinforcement: Brass coated steel wire
Temperature: -22°F to +200°F

KIH CHILLER HOSE

Size : 4" - 10"



Application: Water discharge applications in construction, industry, and agriculture.
Tube: Synthetic rubber
Cover: Weather and ozone resistant synthetic rubber
Reinforcement: High-tensile synthetic textile
Temperature: -13° F to +158°F
Couplings: Contact KIH for proper fitting recommendation and coupling procedure.



KEY INDUSTRIAL HOSE



Part A:
Male Cam x Female NPT
Aluminum
Size (in): 2"-12"



Part B:
Female Cam x Male NPT
Aluminum
Size (in): 2"-12"



Part C:
Female Cam x Hose Barb
Aluminum
Size (in): 2"-12"



Part D:
Female Cam x Female NPT
Aluminum
Size (in): 2"-12"



Part E:
Male Cam x Hose Barb
Aluminum
Size (in): 2"-12"



Part F:
Male Cam x Male NPT
Aluminum
Size (in): 2"-12"



Dust Cap Aluminum
Size (in): 2"-12"



Dust Plug Aluminum
Size (in): 2"-12"



Male Bauer x Shank
Size (in): 2"-12"



Female Bauer x Shank
Size (in): 2"-12"



Male Bauer x Male NPT
Size (in): 2"-8"



Female Bauer x Male NPT
Size (in): 2"-8"



Male Bauer x Female NPT
Size (in): 2"-8"



Female Bauer x Female NPT
Size (in): 2"-8"



KEY INDUSTRIAL HOSE



Male x Female Bauer 45°
Size (in): 2"-12"



Male x Female Bauer 90°
Size (in): 2"-12"



Male Bauer x Flange
Size (in): 2"-12"



Female Bauer x Flange
Size (in): 2"-12"



Bauer Increacer
Size (in): 4"F x 6"M
6"F x 8"M



Bauer Reducer
Size (in): 6"F x 4"M
8"F x 6"M



Male Bauer Plug
Size (in): 4"-8"




Female Bauer Cap
Size (in): 4"-8"



Male Bauer Strainer
Size (in): 4"-12"



Bauer O-Ring
Size (in): 4"-12"




WYE's & TEE's
Size (in): 2"-12"



Galvanized Bauer Pipe
Size (in): 12"



Accessory Cage
Size (in): 44 x 48 x 40



Pipe Racks
Size: LG, XL