



KIH MILL

Keeping You Connected



Application: Medium pressure water discharge hose
Tube: SBR
Cover: 100 % Polyester
Temperature: -25°F to 185°F
Lengths: 50 ft. and 100 ft. stock lengths
Color: White
Couplings: Camlock or Water Shank or NST

Single Jacket						
Part #	ID in	WP psi	Test Pressure psi	Weight lbs	Standard 50' Length Camlock	Standard 50' Length Water Shank
SJ15-150W	1.5	150	250	0.23	SJ15-150W-50-1515ACL	SJ15-150W-50-1515AWS
SJ20-150W	2	150	250	0.28	SJ20-150W-50-2020ACL	SJ20-150W-50-2020AWS
SJ25-150W	2.5	150	250	0.39	SJ25-150W-50-2525ACL	SJ25-150W-50-2525AWS
SJ30-150W	3	150	250	0.50	SJ30-150W-50-3030ACL	SJ30-150W-50-3030AWS
SJ40-150W	4	150	250	0.66	SJ40-150W-50-4040ACL	SJ40-150W-50-4040AWS

Double Jacket						
Part #	ID in	WP psi	Test Pressure psi	Weight lbs	Standard 50' Length Camlock	Standard 50' Length Water Shank
DJ15-250W	1.5	250	300	0.26	DJ15-250W-50-1515ACL	DJ15-250W-50-1515AWS
DJ20-250W	2	250	300	0.33	DJ20-250W-50-2020ACL	DJ20-250W-50-2525AWS
DJ25-250W	2.5	250	300	0.45	DJ25-250W-50-2525ACL	DJ25-250W-50-2525AWS
DJ30-250W	3	250	300	0.607	DJ30-250W-50-3030ACL	DJ30-250W-50-3030AWS
DJ40-250W	4	250	300	0.849	DJ40-250W-50-4040ACL	DJ40-250W-50-4040AWS