



KIH ORANGE & CLEAR

Keeping You Connected



Application: Water suction and rental/construction pumping
Construction: Flexible PVC, rigid PVC helix, synthetic braiding, smooth bore, corrugated O.D.
Temperature: -13°F to + 140°F

Features:

- Lightweight and flexible
- External helix provides for easy drag
- Clear sidewall permits visual check of material flow

Part #	ID in	OD in	Weight lbs/ft	Std Length ft	WP psi	Vacuum Rating in/hg	Min Bend Radius in
OC20-1000	2	2.56	0.86	100	100	28	2.5
OC30-1000	3	3.7	1.24	100	100	28	6
OC40-500	4	4.74	2.15	100	50	28	7.5
OC60-500	6	6.95	3.36	20 or 100	50	28	10
OC80-500	8	9.13	5.71	20	50	28	16.5
OC100-400	10	11.63	8.90	20	40	28	25
OC120-300	12	13.66	10.3	20	30	25	45

Standard Size	Camlock	Bauer
2" x 20'	OC20-1000-20-2020ACL	OC20-1000-20-2020SBU-U
3" x 20'	OC30-1000-20-3030ACL	OC30-1000-20-3030SBU-U
4" x 20'	OC40-500-20-4040ACL	OC40-500-20-4040SBU-U
6" x 20'	OC60-500-20-6060ACL	OC60-500-20-6060SBU-U
8" x 20'	OC80-500-20-8080ACL	OC80-500-20-8080SBU-U
12" x 20'	OC120-300-20-120120ACL	OC120-300-20-120120SBU-A-U

