



Keeping You Connected



KIH RUBBER COVER HD

Construction: 100% high tenacity synthetic polyester yarn, circularly woven and completely protected by a through-the-weave extruded PVC/Nitrile rubber, forming a single homogeneous construction without the use of glues or adhesives of any type

Abrasion Resistance: Made to withstand 10,000 cycles on the Taber Abrasion Machine (H-22 Wheel: 0.5 kg) without exposing the liner.

Couplings: Options are as required by purchaser, expansion ring threaded, Storz clamp ring, etc. Barcode recess available at additional charge.

Temperature: Suitable range -4°F to 176°F

Lengths: Up to 100ft lengths (Longer bulk lengths available on request)

Additional: Meets or exceeds all requirements of NFPA 1961 for attack hose. Standard Colors: ■ ■ Ask about other options

- Lightweight, greater flexibility and virtually kink-free
- Raised thick rib construction, resists cuts, punctures, impact and abrasion
- Through-the-weave design for increased durability
- Heat, chemical and ozone resistant
- Easy to clean, easy to pack

Part #	Diameter (in)	Service Test PSI	Proof Test PSI	Burst Test PSI	Bowl Size (in)	Weight lbs/ft
RC10-600	1	300	600	900	1 3/16"	0.15
RC15-600	1 1/2"	300	600	900	1 13/16"	0.24
*RC17-600	1 3/4"	300	600	900	1 15/16"	0.28
RC20-600	2"	300	600	900	2"	0.32
*RC25-600	2 1/2"	300	600	900	2 13/16"	0.48

*UL Listed to 250 psi

