



KIH RUBBER COVER

Keeping You Connected



Construction: 100% high tenacity synthetic polyester yarn, circularly woven, and completely protected by a through-the-weave extruded PVC/Nitrile rubber, forming a single homogeneous construction without the use of glues or adhesives of any type

Abrasion Resistance: Made to withstand 10,000 cycles on the Taber Abrasion Machine (H-22 Wheel: 0.5 kg) without exposing the liner.

Couplings: Options are as required by purchaser, expansion ring threaded, Storz clamp ring, etc.

Temperature: Suitable range -4°F to 176°F

Lengths: Up to 100ft lengths (Longer bulk lengths available on request)

Additional: Meets or exceeds requirements of NFPA 1961
Standard Colors: ■ ■ Ask about other options

- Lightweight, large diameter with superior flow capability
- Raised thin rib construction, resists cuts, punctures, impact, and abrasion
- Through-the-weave design for increased durability
- Heat, chemical and ozone resistant

Part #	Diameter (in)	Service Test PSI	Proof Test PSI	Burst Test PSI	Bowl Size (in)	Weight lbs/ft
*RC15-500	1 1/2"	250	500	750	1 13/16"	0.22
RC17-500	1 3/4"	250	500	750	1 5/16"	0.25
*RC20-500	2"	250	500	750	2 1/4"	0.3
*RC25-500	2 1/2"	250	500	750	2 13/16"	0.4
**RC30-600	3"	300	600	900	3 3/8"	0.6
***RC40-500	4"	250	500	750	4 1/4"	0.74
***RC50-450	5"	225	450	675	5 1/4"	0.93
RC60-450	6"	225	450	675	6 1/4"	1.35

*UL Listed to 250 psi | **UL Listed to 300 psi | ***UL Listed to 200 psi |

