



KIH 700 SS METAL

Keeping You Connected



Construction: SS 316L Corrugated Flexible Hose with SS 304 Double Wire Braiding

Couplings: TIG Welded with 150# SS 316 Fixed x Float Flanges w/ SS 316 Sch.40 Stub ends

Quality Certifications & Testing:

- Hydrostatic and Pneumatically tested.
- ISO14001:2004
- PED Certified

Part #		ID in	Nom id in	Nom od in	Static Bend Radius in	Dynamic Bend Radius in	Max WP PSI	Weight lbs	
10'	20'							10'	20'
BH20-870SS-10-2020SSFL	BH20-870SS-20-2020SSFL	2	1.98	2.77	5	15	867	44	76
BH30-526SS-10-3030SSFL	BH30-526SS-20-3030SSFL	3	3.15	3.99	9	22	526	61	103
BH40-464SS-10-4040SSFL	BH40-464SS-20-4040SSFL	4	4.36	5.06	10	24	455	98	163
BH60-319SS-10-6060SSFL	BH60-319SS-20-6060SSFL	6	5.93	7.12	18	31	312	163	277
BH80-275SS-10-8080SSFL	BH80-275SS-20-8080SSFL	8	7.76	9.29	19	37	270	251	421
BH100-174SS-10-100100SSFL	BH100-174SS-20-100100SSFL	10	9.86	11.45	25	51	174	267	423
BH120-151SS-10-120120SSFL	BH120-151SS-20-120120SSFL	12	11.82	13.5	31	61	151	353	553

