



# KIH TANK TRUCK

*Keeping You Connected*



**Application:** For use on tank trucks, bulk petroleum stations and in-plant oil service

**Tube:** Oil resistant, black conductive Nitrile(NBR)

**Reinforcement:** Synthetic textile and steel helix steel wire

**Cover:** Black, abrasion, ozone, weather, heat and oil resistant neoprene rubber

**Temperature:** Suitable for use in the range -31°F to 180°F

**Branding:** KIH Tank Truck 150

**Couplings:** Contact KIH for coupling recommendation

Part #	ID in	OD in	WP psi	Weight lb/ft	Bend Radius in
TT20-150K	2	2.48	150	1.1	7
TT30-150K	3	3.5	150	1.86	9
TT40-150K	4	4.61	150	2.72	15
TT60-150K	6	6.69	150	5.21	26
TT80-150K	8	8.9	150	8.4	40

Standard Size	Camlock	Flange
2" x 20'	TT20-150K-20-2020ACL	TT20-150K-20-2020SFL
3" x 20'	TT30-150K-20-3030ACL	TT30-150K-20-3030SFL
4" x 20'	TT40-150K-20-4040ACL	TT40-150K-20-4040SFL
6" x 20'	TT60-150K-20-6060ACL	TT60-150K-20-6060SFL
8" x 20'	TT80-150K-20-8080ACL	TT60-150K-20-8080SFL

