



KEY INDUSTRIAL HOSE

KIH RWS 150

Size : 2" - 12"



Application:Water suction and discharge in industrial and construction services.
Tube:Natural and Synthetic Rubber
Cover: Abrasion and weather resistant synthetic rubber
Temperature:-22°F to + 185°F
Reinforcement: High tensile synthetic textile and steel helix wire

KIH ORANGE & CLEAR

Size : 2" - 12"



Application:Water suction and rental/construction pumping
Construction:Flexible PVC, rigid PVC helix, synthetic braiding, smooth bore, corrugated O.D.
Temperature:-13°F to + 140°F

KIH GREEN PVC SUCTION

Size : 2" - 4"



Application:For use in suction and discharge in construction and city water services settings.
Construction:Ellipse shaped helix, light weight and highly flexible PVC tube with smooth inner and outer surface.
Temperature:-5° F to +140°F

KIH PETROLEUM DROP

Size : 2" - 4"



Application:Heavy duty oil suction for gasoline, diesel fuel, high aromatics, oil slurry, & animal fats handling.
Tube:Safety OHM ground wire embedded in the NBR/PVC tube with smooth bore
Reinforcement:Single braid high tensile polyester yarn with rigid PVC helix.
Temperature:-5° F to +140°F
Features:Copper wire for grounding

KIH TANK TRUCK 150

Size : 2" - 8"



Application:For use on tank trucks, bulk petroleum stations and in- plant oil service
Tube:Oil resistant, black conductive Nitrile(NBR)
Reinforcement:Synthetic textile and helix steel wire
Cover:Black, abrasion, ozone, weather, heat and oil resistant neoprene rubber
Temperature:Suitable for use in the range -31°F to 180°F

KIH OIL SERVICES & DISCHARGE CARGO

Size : 4" - 24"



Application:For oil/water suction and delivery service
Tube:Oil and fuel resistant conductive nitrile (NBR)
Cover:Oil, weather and ozone resistant, wrapped cover, black synthetic rubber
Temperature:-40°F to +194°F
Reinforcement:Multiple high tensile synthetic tire cords (polyester cords) with steel wire helix
Couplings:Built-in pipe flanges fixed x floating

KIH COMPOSITE 250

Size : 4" - 12"



Application:Suction and Discharge of Water, Gasoline, Diesel fuel, Paraffin, Kerosene, Lubricating Oils, 100% aromatics, black oils and heavy lubricants and solvents.
Body:Multiple layers of polypropylene fabric, film and
Reinforcement:polyester barrier layers
High tensile strength galvanized inner and outer wire
Temperature:-22°F to +176°F(-30°C to +80°C)
Cover:Abrasion resistant PVC impregnated fabric

KIH SS 700 METAL

Size : 2" - 12"



Construction:SS 316L Corrugated Flexible Hose with SS 304 Double Wire Braiding
Couplings:TIG Welded with 150# SS 316 Swivel Flanges at both ends with SS 316 Sch.40 Stub end.

KIH CHEMICAL TRANSFER

Size : 2" - 6"



Tube:Clear Ultra High Molecular Weight polyethylene
Cover:Green abrasion resistant green EPDM
Reinforcement:Multiple plies of high tensile textile with dual helix
Temperature:-40°F to +250°F

KIH HT MATERIAL HANDLING

Size : 4" - 8"



Application:High temperature abrasive handling flying ash, rock, sand and other abrasive materials in a vacuum truck application.
Construction:Flexible EPDM rubber tube, polyethylene helix with metal helical wire
Temperature:-40° F to +220°F
Features:Metal wire for grounding



KEY INDUSTRIAL HOSE

KIH RUBBER COVER

Size : 1.5" - 6"



Construction: 100% high tenacity synthetic polyester yarn, circularly woven, and completely protected by a through-the-weave extruded PVC/Nitrile rubber, forming a single homogeneous construction without the use of glues or adhesives of any type

Abrasion Resistance: Made to withstand 10,000 cycles on the Taber Abrasion Machine (H-22 Wheel: 0.5 kg) without exposing the liner.

Temperature: Suitable range -4°F to 176°F

Additional: Standard colors:   Ask about other options

KIH RUBBER COVER HD

Size : 2" - 3"



Construction: 100% high tenacity synthetic polyester yarn, circularly woven and completely protected by a through-the-weave extruded PVC/Nitrile rubber, forming a single homogeneous construction without the use of glues or adhesives of any type

Abrasion Resistance: Made to withstand 10,000 cycles on the Taber Abrasion Machine (H-22 Wheel: 0.5 kg) without exposing the liner.

Temperature: Suitable range -4°F to 176°F

Additional: Standard colors:   Ask about other options

KIH NITRILE 150 DISCHARGE

Size : 2" - 12"



Tube: Blend of synthetic elastomers, smooth, oil resistant, black

Reinforcement: Single high tensile textile braid

Cover: Blend of synthetic elastomers compound, ribbed finish

Temperature: Suitable range -4°F to 176°F

Colors: Black, Orange, Red or Yellow

KIH MILL

Size : 1.5" - 4"



Application: Medium pressure water discharge hose

Tube: SBR

Cover: 100 % Polyester

Temperature: -25°F to 185°F

Lengths: 50 ft. and 100 ft. stock lengths

Color: White

Couplings: Camlock or Water Shank or NST

KIH RED PVC DISCHARGE

Size : 2" - 12"



Application: Use for agricultural, quarry, irrigation, mining construction and industrial applications

Tube & Cover: Premium Red PVC

Reinforcement: Two spiral plies and longitudinal silk cords

Temperature: -10°F to 150°F

Couplings: Standard short shank aluminum, malleable or brass couplings, Steel Bauer

KIH BLUE PVC DISCHARGE

Size : 2" - 6"



Application: Use for light duty, general purpose agricultural, irrigation, and construction applications.

Tube & Cover: Blue PVC

Reinforcement: Polyester yarn

Temperature: -4°F to 150°F

Packaging: Cut and coupled to length

KIH RUBBER WATER DISCHARGE

Size : 4" - 10"



Application: Water discharge applications in construction, industry, and agriculture.

Tube: Synthetic rubber

Cover: Weather and ozone resistant synthetic rubber

Reinforcement: High-tensile synthetic textile

Temperature: -13° F to +158°F

KIH TPU DISCHARGE

Size : 6" - 16"



Application: Water transfer, Oilfield, Fracking

Tube & Cover: TPU, Smooth cover, extruded through the weave.

Reinforcement: Circular woven filament polyester yarn.

Temperature: -58°F to +176°F

KIH WIRE BRAID AIR BULL

Size : 2" - 4"



Application: Heavy Duty air hose for use in mines, construction and industrial applications where maximum service is required

Tube: Blend of SBR and NBR, black, smooth, suitable for water and air, resistant to oil mist

Cover: Blend of EPDM and SBR, yellow, smooth with cloth impression, weather, ozone and abrasion resistant

Reinforcement: Brass coated steel wire

Temperature: -22°F to +200°F

Scan to visit a Digital Catalog



Connect with us:



334.417.0019

©2023 KIH LLC. All Rights Reserved

117 S. INDUSTRIAL BLVD
ENTERPRISE, AL 36330

WWW.KIHLLC.COM
SALES@KIHLLC.COM



KEY INDUSTRIAL HOSE



Part A:
Male Cam x Female NPT
Aluminum
Size (in): 2"-12"



Part B:
Female Cam x Male NPT
Aluminum
Size (in): 2"-12"



Part C:
Female Cam x Hose Barb
Aluminum
Size (in): 2"-12"



Part D:
Female Cam x Female NPT
Aluminum
Size (in): 2"-12"



Part E:
Male Cam x Hose Barb
Aluminum
Size (in): 2"-12"



Part F:
Male Cam x Male NPT
Aluminum
Size (in): 2"-12"



Dust Cap Aluminum
Size (in): 2"-12"



Dust Plug Aluminum
Size (in): 2"-12"



Male Bauer x Shank
Size (in): 2"-12"



Female Bauer x Shank
Size (in): 2"-12"



Male Bauer x Male NPT
Size (in): 2"-8"



Female Bauer x Male NPT
Size (in): 2"-8"



Male Bauer x Female NPT
Size (in): 2"-8"



Female Bauer x Female NPT
Size (in): 2"-8"



KEY INDUSTRIAL HOSE



Male x Female Bauer 45°

Size (in): 2"-12"



Male x Female Bauer 90°

Size (in): 2"-12"



Male Bauer x Flange

Size (in): 2"-12"



Female Bauer x Flange

Size (in): 2"-12"



Bauer Increacer

Size (in): 4"F x 6"M
6"F x 8"M



Bauer Reducer

Size (in): 6"F x 4"M
8"F x 6"M



Male Bauer Plug

Size (in): 4"-8"



Female Bauer Cap

Size (in): 4"-8"




Male Bauer Strainer

Size (in): 4"-12"



Bauer O-Ring

Size (in): 4"-12"



WYE's & TEE's

Size (in): 2"-12"




Galvanized Bauer Pipe

Size (in): 12"



Accessory Cage

Size (in): 44 x 48 x 40



Pipe Racks

Size: LG, XL