



# KIH OIL SUCTION & DISCHARGE CARGO

*Keeping You Connected*



**Application:** For oil/water suction and discharge service

**Tube:** Oil and fuel resistant conductive nitrile (NBR)

**Cover:** Oil, weather and ozone resistant, wrapped cover, black synthetic rubber

**Temperature:** -40°F to +194°F

**Reinforcement:** Multiple high tensile synthetic tire cords (polyester cords) with steel wire helix

**Lengths:** 10' and 20' standard lengths

**Couplings:** Built-in pipe flanges fixed x floating

**Features:**

- Hose assemblies are hydro-tested and certified at the factory
- Tested following U.S.C.G. certification standards

Part #		ID	OD	WP	Bend Radius	Weight lbs	
10'	20'	in	in	psi	in	10'	20'
OSD40-250K-10-4040SFL	OSD40-250K-20-4040SFL	4	5 1/2	250	19	100	176
OSD60-250K-10-6060SFL	OSD60-250K-20-6060SFL	6	7 1/2	250	19	183	265
OSD80-250K-10-8080SFL	OSD80-250K-20-8080SFL	8	9 1/2	250	38	214	368
OSD100-250K-10-100100SFL	OSD100-250K-20-100100SFL	10	11 1/2	250	48	342	540
OSD120-250K-10-120120SFL	OSD120-250K-20-120120SF	12	13 3/4	250	48	503	732
OSD140-250K-10-140140SFL	OSD140-250K-20-140140SFL	14	15 3/4	250	68	573	845
OSD160-250K-10-160160SFL	OSD160-250K-20-160160SFL	16	17 3/4	250	78	765	1130
OSD180-250K-10-180180SFL	OSD180-250K-20-180180SFL	18	20	250	106	946	1408
OSD240-250K-10-240240SFL	OSD240-250K-20-240240SFL	24	27	250	168	1575	2250

