



KIH RUBBER WATER SUCTION

Keeping You Connected



Application: Water suction and discharge in industrial and construction services.

Tube: Natural and Synthetic Rubber

Cover: Abrasion and weather resistant synthetic rubber

Temperature: -22°F to + 185°F

Reinforcement: High tensile synthetic textile and steel helix wire

Part #	ID In	OD in	WP psi	Burst psi	Bend Radius in	Weight lbs/ft
RWS20-150K	2	2.4	150	450	9	1.03
RWS30-150K	3	3.46	150	450	14	1.66
RWS40-150K	4	4.65	150	450	28	2.96
RWS60-150K	6	6.61	150	450	37	5.18
RWS80-150K	8	8.78	150	450	43	8.40
RWS100-150K	10	10.79	150	450	45	12.42
RWS120-150K	12	12.95	150	450	75	18.35

Standard Size	Camlock	Bauer
2" x 20'	RWS20-150K-20-2020ACL	RWS20-150K-20-2020SBU-U
3" x 20'	RWS30-150K-20-3030ACL	RWS30-150K-20-3030SBU-U
4" x 20'	RWS40-150K-20-4040ACL	RWS40-150K-20-4040SBU-U
6" x 20'	RWS60-150K-20-6060ACL	RWS60-150K-20-6060SBU-U
8" x 20'	RWS80-150K-20-8080ACL	RWS80-150K-20-8080SBU-U
10" x 20'	RWS100-150K-20-100100ACL	RWS100-150K-20-100100SBU-A-U
12" x 20'	RWS120-150K-20-120120ACL	RWS120-150K-20-120120SBU-A-U

